



Instruction manual for the movable wall – semiautomatic

As of 04/2013

AWA

Contents

1	Introduction.....	3
2	Product description.....	3
3	Safety rules.....	3
4	Intended use.....	3
5	Operating the movable wall.....	4
	5.1 General information.....	4
	5.2 Operating the movable wall.....	5
	5.2.1 The control panel.....	5
	5.2.2 Opening movable wall.....	6
	5.2.3 Panel movement.....	6
	5.2.4 Closing movable wall.....	9
	5.2.5 After the building up and dismantling of the movable wall panel.....	9
6	Technical data.....	10
7	Guarantee.....	10
8	Problem solving.....	10
9	General cleaning instructions.....	11
10	Taking out of operation.....	12
11	Disposal.....	12
12	Adress of manufacturer.....	12

1 Introduction

Dear customer,

Thank you for buying our movable wall system with semiautomatic control.

You have acquired a state-of-the-art quality product, which was produced according to the recognised rules of technology.

Please read this instruction manual carefully, follow the safety instructions and keep this manual for future reference.

3 Safety rules

The operator may only carry out any work or settings, which are described in this manual.

Children must not operate this movable wall system.

To guarantee a smooth operation of your mobile movable wall, please follow all the instructions, described in this manual.

2 Product description

The semiautomatic operated movable wall system comes as a complete system ready to simply plug in to the mains.

The panels are moved manually one by one into the wall post, which provides the panels with electricity.

The provided control panel offers you greater comfort and user-friendliness. The upper and lower pressure seals can be extended or retracted electronically within approx. 4 seconds at the push of a button.

An integrated emergency battery has also been provided to guarantee that you are always able to dismantle the semiautomatic controlled movable wall system even in the event of a power failure.

4 Intended use

- The product is a semiautomatic controlled movable wall system.

It allows you to functionally and flexibly divide rooms up into more rooms.

Other use of any form is not permitted and can be dangerous for both the operator and others.

Any damage caused by other uses will not be covered by the manufacturer. The manufacturer cannot be held liable in this case.

- The initial start-up of the semiautomatic controlled movable wall must be carried out by an installation company, which is certified by the company Nüsing.
- The movable wall is intended only for dry interior rooms.

5 Operating the movable wall

5.1 General information.

The wall(s) should only be operated by fully trained personnel. Due to a danger of crushing, make sure there are no body parts or other objects in the range of the vertical pressure seals, when they extend.

Always move the panels at walking pace with the male profile side (facing you) (See pic. 1).

Please note: *If the panel weighs more than 350Kg you must use a stopper. (See pic. 2 – 3).*

Always place the stopper on the inter-panel joint of the telescopic wall post or of an already positioned panel.

After reaching the panel's position, remove the stopper and gently connect the two panels together.

To achieve the best sound insulation, the wall(s) must always be built up perfectly plumb. Make sure that all the pressure seals have fully extended.

On (wicket) door panels, the operation of the seals on the door leaf is controlled by the mechanism in the door stile at the bottom on the hinge side.

Our movable walls don't need any maintenance! We recommend, however, an annual inspection by our service team.



Pic. 1: Panel movement



Pic. 2 – 3: left stopper, right stopper in use

5.2 Operating the movable wall

Please make sure that all wicket doors are closed, before starting to build up or dismantle the wall(s).

5.2.1 The control panel

Turn the key in the control panel to activate the system. You can now carry out the following procedures:

🔒 "Close mobile wall"

When all the panels are in position, press the symbol "close" once (see pic. 4) to activate the pressure seals of the panels to extend.

🔓 "Open mobile wall"

When all the panels are in position, press the symbol "open" once (see pic. 5) to activate the pressure seals of the panels to retract.

"Zero/neutral position"

In this position (see pic. 6) the wall is deactivated and the key must be removed.



Pic. 4: control panel mode "close movable wall"



Pic. 5: control panel mode "open movable wall"



Pic. 6: control panel mode "zero/neutral position"



Pic. 7: Movable wall – semiautomatic operating system

5.2.2 Opening movable wall

By pressing the symbol "open" once on the control panel (see pic. 5), you start the process of dismantling the wall (the symbol "open movable wall" on the control panel lights up continuously.)

The vertical telescopic element of the so-called retractable wall post retracts automatically. As soon as it has fully retracted from (the tongue and groove connection of) the next panel, the horizontal pressure seals of the panels open automatically. When this process is completed and the "open movable wall" on the control panel is blinking, you can pull the panel out (of the tongue and groove connection) of the next panel. Repeat this procedure until the last panel, regardless of panel suspension and track system.



Step 1:

The vertical telescopic element of the so-called retractable wallpost (AWA) retracts. Afterwards the horizontal pressure seals open automatically (no. 1).



Step 2:

Panel no. 1 can be detached from panel no. 2.



Step 3:

The horizontal pressure seals of the following panel no. 2 now open automatically.

Pic. 8: Example of the opening procedure of panels with a single point suspension system.

5.2.3 Panel movement

The way the panels are moved depends on the suspension system of the panels and can be divided up as follows:

- Panel movement with single point suspension



Step 1:

Turn the panel through 90 degrees (no.1).



Step 2:

Move the panel no.1 at right angles to the tracks into the parking area in front of the wall. The horizontal pressure seals of panel no. 2 retract automatically.



Step 3:

You can now detach panel no. 2 from panel no. 3.



Step 4:

Now move panel no. 2 in the same way as panel no. 1 into its final parking position.

Pic. 9: Example of the panel movement with a single point suspension.

- Panel movement with a two point suspension



Step 1:

Move panel no. 1 until the top roller reaches the branch track whilst pushing the top roller into the branch track.



Step 2:

Move panel no. 1 into its final parking position. The horizontal pressure seals of panel no. 2 retract automatically



Step 3:

You can now detach panel no. 2 from panel no. 3



Step 4:

Move panel no. 2 until the top roller reaches the branch track whilst pushing the top roller into the branch track. Move panel no. 2 into its final parking position.

Pic. 10: Example of panel movement with a two point suspension.

Please note: *When you build up the movable wall, you move the panels in the reverse order.*



5.2.4 Closing movable wall

By pressing the symbol "close" once on the control panel (see pic. 11), you start the process of building up the wall (the symbol "close movable wall" on the control panel lights up continuously.)

The first panel is moved out of the parking area with the female side first and moved into the male connection of the wall post. The horizontal pressure seals extend automatically. The optimal pressure has been reached as soon as seals have completely extended. The control panel symbol "close movable wall" will now blink and the next panel can be put into position. Repeat this procedure until you reach the retractable wall post.

You have to press both of the control panel symbols simultaneously and constantly so that the vertical telescopic element of the retractable wall post can extend. When the telescopic element has reached its optimal pressure the control panel symbol "close movable wall" will now blink.

In the event of a dangerous situation (e.g. an object in the range of the telescopic element) release the symbols to deactivate. The telescopic element will stop immediately and start to retract. This also means that the pressure seals of the last positioned panel will retract.

When the danger is over the control system has to be reset. To do this simply turn the control panel key to "neutral".

Only now can the signal "close movable wall" (see pic. 11) be activated by reactivating the control panel and the closing of the wall can begin again.

5.2.5 After the building up and dismantling of the movable wall panel.

Turn the control panel key to "neutral" and the remove the key. (see pic. 12).



Pic. 11: Control panel mode "close movable wall"



Pic. 12: Control panel mode "neutral"

6 Technical data

Main control box:

- Input voltage: AC – 230 V - 50 Hz
- Output voltage: DC 24 V
- Power: 115 W
- Max. pressure: 2000 N
- Type of protection: IP 44

7 Guarantee

The movable wall with semiautomatic control is produced according to the recognised rules of technology and is subject to continuous quality controls.

The whole product is guaranteed for up to 5 years.

Nevertheless, should any error occur, please contact our service team immediately.

Damage caused by natural wear and tear, inappropriate use, or unauthorised modification is excluded from this guarantee.

8 Problem solving

The pressure seals don't fully extend or retract:

- Check whether the correct symbol on the control panel was chosen.
- Check whether the movable wall panels were properly joined to each other.
- Check whether mains electricity is switched on.

9 General cleaning instructions

Plastic finishes:

Light, new stains:

- Use paper towels; soft, clean cloth (dry or damp); sponge etc.
- When wet cleaning, wipe dry immediately with absorbent paper towels.

Normal stains:

- Clear, warm water; clean, soft duster or cloth; soft sponge or soft brush (e.g. nylon brush)
- Usual non-abrasive cleaners.
- Apply cleaner on a sponge and apply to the stain, allow to soak according to the severity of the stain. Wash off with clear water or glass cleaner. Repeat if necessary.
- Remove all remaining cleaning material to avoid streaks.
- Wipe the surface dry with absorbent paper towels. Change towels frequently.

Wood finishes:

Light and normal stains:

- Paper towels; soft, clean towels (dry)
- When wet cleaning, wipe dry immediately with absorbent paper towels.

Textile finishes:

Light and normal stains:

- Use a soft brush or a vacuum cleaner.

Sheet steel finishes:

Light, new stains:

- Use paper towels; soft, clean cloth (dry or damp); sponge etc.
- When wet cleaning, wipe dry immediately with absorbent paper towels.

Normal stains:

- Clear, warm water; clean, soft duster or cloth; soft sponge or soft brush (e.g. nylon brush)
- Usual non-abrasive cleaners.
- Work cleaning material into a foam and apply to the stain, allow to soak according to the severity of the stain. Wash off with clear water or glass cleaner. Repeat if necessary.
- Remove all remaining cleaning material to avoid streaks.
- Wipe the surface dry with absorbent paper towels. Change towels frequently.

Warning!

Do not use any abrasive materials (scouring powder, wire wool), polishes, waxes, furniture polish, or bleach for regular cleaning.

Do not use any strong acid or alkaline cleaning materials such as lime scale remover, formic acid, amino sulphates, drain cleaner, hydrochloric acid, silver polish, oven cleaner.

10 Taking out of operation

Should you take the movable wall out of operation, it must be disconnected from the mains and make sure that it cannot be reconnected unintentionally.

Please note: *The mains plug of the movable wall must always be accessible.*

11 Disposal

Please dispose of the movable wall according to current regulations. Information is available from your local council.

Warning: Danger caused by electricity
The main control box runs on 230 V. There is, therefore, an increased danger of electric shocks or even death by electrocution.
As a result any installation, connection or dismantling work should be carried out only by fully trained personnel.
Before any work is carried out on the movable wall, it must be disconnected from the mains.

12 Address of manufacturer



Franz Nüsing GmbH & Co. KG

Borkstraße 5
48163 Münster
(Germany)

Phone: +49 (0)251 780010
Fax: +49 (0)251 780018927

www.nuesing.com
info@nuesing.com